8088 MICROPROCESSOR EXPERIMENTAL UNIT

BY

ANTONIOU MARIOS

Project Report
Submitted to
the Department of Electrical Engineering
of Higher Technical Institute
Nicosia Cyprus
In partial fulfilment of the requirements
for the diploma of
TECHNICIAN ENGINEER
in
ELECTRICAL ENGINEERING

June 1992

Project Supervisor: Mr. M. Kassinopoulos

Type of Project: Individual



PROJECT SUMMARY

This project deals with the study of the various parts and functions of the BGC-8088 microengineer.

It also include study of the communication availabilities between the BGC-8088 microengineer and the PC. Some experiments were carried out so as to be more familiar with the above availabilities.

An interface card which drives Traffic Light was designed and constructed. The interface card is driven with the aid of assembly programs which are transferred from the PC to the BGC-8088 microengineer which generates the appropriate signals. These signals are transferred to the interface card through the parallel control port of the Microengineer.

The operation of Traffic Light was also simulated on the screen of the PC.

CONTENTS

		Page		
Proj	ect Summary			
Intro	oduction			
CHAP'	TER 1 BGC-8088 Microengineer Description			
1.0	Introduction	1		
1.1	.1 BGC-8088 V.30 specifications			
1.2	Functional description of hardware parts of the			
	microengineer which were used in the project	2		
	1.2.1 The 8088 processor	3		
	1.2.2 The 8255 programmable peripheral	4		
	1.2.3 The 8254 programmable interval timer	7		
	1.2.4 The fifty pin edge slot	8		
	1.2.5 8259 Programmable Interrupt controller	10		
	1.2.6 LCD Module	11		
	1.2.7 Status port	11		
1.3	Monitor Commands of BGC8088	11		
Chap	ter 2 Assembler and Debugger			
2.0	Introduction	13		
2.1	Steps followed to convert an assembly program of			
	an executable one	13		
2.2	Assembler description	14		
2.3	Debug descriptions and commands	17		
	2.3.1 Debug description	17		
	2.3.2 Debugger commands	17		
2.4	The Debugging circle	20		
CHAPT	TER 3 PC interface with BGC 8088 microengineer			
3.0	Introduction	21		
3.1	Normal operation of BGC 8088 Microengineer	21		
3.2	Communication availabilities between the			
	BGC 8088 Microengineer and the PC	22		
	3.2.1 Download procedure	23		

		Page
3.3	Memory considerations taken for communication	
	functions	24
3.4	Brief discussion about the two experiments	
	done	26
3.5	Experiment No:1 Controlling the blinking of	
	LED through status port	26
3.6	Experiment No:2 Stop watch with accuracy of	
	1/100 second.	26
CHAI	PTER 4 The Interface Module	
4.0	Introduction	29
4.1	Process followed for correct processing	
	of signals from BGC Microengineer to	
	the interface card	29
4.2	Characteristics - Components Used	32
4.3	Initializing and testing programs for 8255	34
4.4	Testing program for interface card	35
CHAF	PTER 5 Software Development	
5.0	Introduction	37
5.1	Program Requirements	37
5.2	Main Routines used	39
5.3	Delay routine	39
5.4	Breakpoint routine	40
5.5	Lcd Busy routine	41
5.6	Display routine	42
CHAP	PTER 6 Testing	
6.0	Introduction	43
6.1	Software testing	43
6.2	Hardware Testing	44
6.3	Testing of 8255 for High and Low output	
	of port A	44
	6.3.1 Testing of 8255 for High output	
	of port A	44
	6.3.2 Testing of 8255 for Low output	
	of port A	45

		Page		
6.4 Other Tes	ts for 8255 and Interface Card	45		
6.5 Conclusion	ns from testing	45		
6.6 Comments	and Conclusions	46		
Conclusions				
References				
Appendices				
Appendix 1.	BGC 8088 V 3.0 specifications and circuit diagrams.			
Appendix 2.	Data sheets			
Appendix 3.	Microprocessor specifications			
Appendix 4.	8255, 8254 and 8259 Specifications			
Appendix 5.	Experiment Programmes			
Appendix 6.	Program Listing			
Appendix 7.	Testing programs			