HIGHER TEHNICAL INSTITUTE

MECHANICAL ENGINEERING DEPARTMENT

DIPLOMA PROJECT

PROJECT TITLE:

AIR CONDITIONING SYSTEM DESIGN FOR A LARGE BUILDING

PROJECT REPORT SUBMITTED BY:

- 1. APOSTOLIDIS DIMITRIS
- 2. TRINGOS MICHALIS

PROJECT SUPERVISOR:

I. MICHAELIDIS LECTURER, H.T.I.

JUNE 1989

TECHNICAL INSTITUTE 1537

INTRODUCTION

The control of indoor climate is an importand industry in Cyprus and throughout the world generally. Only in a few favored areas of the earth's temperate zones can people live comfortably and work effectively the year round without some form of winter heating and/or summer cooling. The science and practice of creating a controlled climate, that is, conditions that are conducive to human comfort is called air conditioning.

An air conditioning system is a combination of various components which by operating in a controlled manner, produce and maintain the "artificial" comfort environment which is so desirable. The term air conditioning is sometimes misunderstood or misused. Often only cooling is implied when air conditioning is mentioned. However in practice to provide complete air conditioning a system must accomplish all the following: HEATING, HUMIDIFICATION, COOLING, DEHUMIDIFICATION, VENTILATION, FILTERING and CIRCULATION. Systems which omit one or more of the above seven functions are therefore not complete systems.

In Cyprus air conditioning is widely used in business enterprises such as banks, office buildings, shops and hotels, but domestic air conditioning is limited mainly due to its current relatively high initial cost. However, lately domestic air conditioning started becoming quite popular.

Because Cyprus island enjoy a very sunny climate with long periods of bright sunshine and high insolation, a lot of tourists are attracted every year, but especially in the summer period. High demand levels for hotel beds, resulted to the rapid development of hotel industry and many hotels have been erected and other are still under erection, a lot of which are situated near the lovely beaches. Due to the big number of hotels and the need of high capacity air conditioning installations to service

- 5 -

them, the higher percentage of capital expenditure in the air conditioning sector is in the hotel air conditioning field.

The building in concern consist of four flat floors, the ground floor mesanine and the basement. The basement contains mainly stores, equipment rooms, staff rooms and the mechanical room. For the sake of keeping both the initial and running costs of the air conditioning plant as low as possible the basement rooms will not conditioned.

On the other hand ground floor and mesanine contains shops that must be conditioned.

The foor floors contain the Flats, 4 each which wil be fully air-conditioned. Again for keeping initial and running expenses down the corridors will not be conditioned.

-б-

| | Introduction | Page 5 |
|-------|---------------------------------------|-----------|
| | · | |
| | Chapter 1 | |
| 1. | U-values estimation | 7 |
| 1.1 | Definition of U-value | 8 |
| 1.2 | Definition of terms used for the | 13 |
| | calculation of U-values | |
| 1.3 | Calculation of U-values | 18 |
| | Chapter 2 | |
| 2.1 | Design conditions | 23 |
| 221.1 | Outside Design conditions | 23 |
| 2.1.2 | Insite Design conditions | 23 |
| 2.2 | Selection of insite conditions | 25 |
| | Chapter 3 | |
| 3. | Analysis of the air conditioning load | 26 |
| | | |
| | Part 1 Cooling load | 29 |
| 3.1 | Introduction | 30 |
| 3.1.1 | Load classification | 30 |
| 3.1.2 | System installation loads | 32 |
| 3.1.3 | Further load classification | 33 |
| 3.1.4 | Variability of cooling load | 34 |
| 3.2 | Solar heat gain through glass | 37 |
| 3.2.1 | Introduction | 37 |
| 3.2.2 | Solar heat gain values | 38 |
| 3.2.3 | Heat storage | 39 |
| 3.2.4 | Shading | 40 |
| 3.3 | Heat gain due to Infiltration and | 44 |
| | ventilation | |
| 3.3.1 | Sensible heat component | 44 |
| 3.3.2 | Laten heat component | 45 |

| | | Page |
|-------|--|-------|
| | Part 2::Heating load | 47 |
| 3.4 | Heating load | 48 |
| 3.4.1 | Sensible heat load | 43 |
| 3.4.2 | Laten head load | 48 |
| 3.5 | Simplicity of heating load estimation | 48 |
| 3.5.1 | Winter loads classification | 49 |
| 3.5.2 | Structural or transmission losses | 49 |
| 3.5.3 | Heating load due to ventilation and | 50 |
| | infiltration | |
| 3.6 | The Crankage Method | 52 |
| 3.7 | Assuptions for heating load | 54 |
| | calculations | |
| 3.8 | Groups of rooms with identical loads | 54 |
| | | |
| | Chapter 4 | |
| 4. | Air conditioning system selection | 55 |
| 4.1 | Alternative solutions for use | 56 |
| 4.1.1 | Heat pump for cooling and heating | 56 |
| 4.1.2 | Fun coil units | 56 |
| 4.1.3 | Only cooling split units with | 56 |
| | ratiators for heating | |
| 4.2 | Air conditioning system objectives | 57 |
| 4.3 | Classification of air conditioning | . 57 |
| | systems | |
| 4.3.1 | Classification as to season of the year | 58 |
| 4.3.2 | Classification as to equipment arrangeme | ent59 |
| 4.3.3 | Central station systems | 61 |
| 4.3.4 | Combination Systems | 68 |
| 4.4 | Air conditioning system components | 68 |
| | | |
| | Chapter 5 | |
| 5.1 | Computer forms | 74 |
| 5.2 | Explanation of the computer forms | 206 |
| 5.3 | Computer results | 212 |
| 5.4 | Sample calculation | 218 |

,

•

| | | <u>ruge</u> |
|------|----------------------------------|-------------|
| | Chapter 6 | |
| 6.1 | System selection | 234 |
| 6.2 | Selection of the chiller | 236 |
| 6.3 | Selection of the boiler | 238 |
| 6.4 | Selection of the burner | 238 |
| 6.5 | Selection of the boiler flue | 239 |
| 6.6 | Selection of the expansion tank | 240 |
| 6.7 | Selection of the oil tank | 241 |
| 6.8 | Selection of the pump | 242 |
| 6.9 | Selection of the FCU | 243 |
| 6.10 | Selection of Radiators | 247 |
| 6.11 | Energy meters | 248 |
| 6.12 | Selection of grilles and extract | |
| | units for bathrooms | 248 |
| 6.13 | Piping | 249 |
| | | |
| | Chapter 7 | |
| 7. | Installation of equipments | 250 |
| 7.1 | Boiler | 251 |
| 7.2 | Burner | 253 |
| 7.3 | Boiler flue | 253 |
| 7.4 | Air cooled water chiller | 254 |
| 7.5 | Fun coil units | 257 |
| 7.6 | Pumps | 258 |
| 7.7 | Piping | 260 |
| 7.8 | Pipework supports | 262 |
| 7.9 | Insulation | 263 |
| 7.10 | Oil storage tank | 264 |
| 7.11 | Toilet Ventilators | |
| 7.12 | Valves | 264 |
| | Chapter 8 | |
| 8 | Maintenance | 0.65 |
| 0. | | 265 |

| 8.1 | Introductory | 266 |
|-----|--------------|-----|
| 8.2 | Boiler | 266 |

5

Pages

| 8.3 | Burner | 267 |
|-----|------------------------------|-----|
| 8.4 | Pumps | 268 |
| 8.5 | Air filters | 269 |
| 8.6 | Chiller | 269 |
| | ş ¹ | |
| | Chapter 9 | |
| 9.1 | Cost analysis | 272 |
| 9.2 | Conclusions | 274 |
| | | |
| | Chapter 10 | |
| | Detail drawing of equipments | 278 |
| | | |
| | Chapter 11 | |
| | Appendices | |
| | | |

na anna an Aonaichtean an Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean A An Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean Aonaichtean A

A second s