

HIGHER TECHNICAL INSTITUTE

ELECTRICAL ENGINEERING DEPARTMENT

DIPLOMA PROJECT

DESIGN OF THE ELECTRICAL SERVICES OF A HOTEL

by

ADONIS KALLIS (E/955)

JUNE 1995

**DESIGN OF THE ELECTRICAL
SERVICES OF A HOTEL**

BY

ADONIS KALLIS

Project Report

**Submitted to
the department of Electrical Engineering
of the Higher Technical Institute
Nicosia, Cyprus
in partial Fulfillment of the
requirements for the diploma of**

**TECHNICIAN ENGINEER
IN
ELECTRICAL ENGINEERING**

June 1995

2434

CONTENTS

	Page
ACKNOWLEDGEMENTS	5
ABSTRACT	6
SYMBOLS AND ABBREVIATIONS	7
INTRODUCTION	8
CHAPTER 1	
ILLUMINATION	
1.1 INTRODUCTION	11
1.2 UNITS AND DEFINITIONS	11
1.3 ELECTRIC LAMPS	12
1.4 RULES FOR ENERGY EFFICIENT LIGHTING	13
1.5 METHODS OF ILLUMINATION CALCULATIONS	14
1.6 ACTUAL DESIGN	16
1.7 TYPE OF FITTING USED	18
RESULTS OF ILLUMINATION DESIGN	19
CHAPTER 2	
LIGHTING AND POWER REQUIREMENTS	
2.1 GENERAL	31
2.2 FUNDAMENTAL REQUIREMENTS FOR SAFETY	31
2.3 DESIGN PROCEDURE	32
2.4 ACTUAL DESIGN PROCEDURE	35
RESULTS OF LIGHTING CIRCUITS	45
RESULTS OF SOCKET OUTLETS CIRCUITS	48
FAULT LEVEL CALCULATIONS	61

CHAPTER 3

SAFETY AND EARTHING

3.1	GENERAL	66
3.2	SITUATIONS WHERE SPECIAL PRECAUTIONS ARE USED	66
3.3	DEFINITIONS	67
3.4	PROTECTION FOR SAFETY	68

CHAPTER 4

TELEPHONE DISTRIBUTION

4.1	DEFINITIONS	72
4.2	CONDUITS AND CONDUIT SIZES	73
4.3	INSTALLATION OF THE DISTRIBUTION CASES	74
4.4	INSTALLATION OF TELEPHONE LINES	75
4.5	LIST OF CONNECTIONS	78

CONCLUSIONS

APPENDICES

REFERENCES

ACKNOWLEDGEMENTS

I would like to express my sincere appreciation and thanks to my project supervisor Mr Michael for his guidance and assistance given throughout the project period.

Also I would like to thank all those who in any way helped me and gave me courage during the design period of this project.

ABSTRACT

This project deals with the design of the Electrical Services of a Hotel. The electrical services are the Lighting, power and telecommunication installation. This work has been divided into chapters as follows:

CHAPTER 1: This chapter deals with the illumination design and in accordance with the CIBS code we can find the level of illumination of the various areas.

CHAPTER 2: This chapter deals with the power and lighting circuits in accordance with the IEE regulations as currently amended and the local EAC conditions of supply.

CHAPTER 3: This chapter deals with safety and earthing.

CHAPTER 4: This chapter deals with the telephone distribution design of the hotel in accordance with CYTA requirements.

The necessary pictures, catalogues and information are given in the appendices.

The drawing of the electrical installation of the hotel are also included.

SYMBOLS AND ABBREVIATIONS

MDB	Main Distribution board
DB	Distribution board
AC	Alternative current
DC	Direct current
MDC	Main Distribution Case
DC	Distribution case
IEE	Institution of Electrical Engineers
EAC	Electricity authority of Cyprus
MCB	Miniature circuit breakers
MCCB	Moulded Case Circuit Breakers
RCCB	Residual Current Circuit Breakers
PVC	Polyvinyl Chloride
CPC	Circuit protection Conductor
CSA	Cross Sectional Area
SWA	Steel Wire Armoured
EFLI	Earth fault loop impedance
PF	Power Factor
CCT	Circuit
VD	Voltage Drop
F01L1	Lighting circuit L1 supplied by Distribution board of flat 01 in the Ground Floor.
S/O	Socket Outlet

INTRODUCTION

This project deals with the design of the Electrical Services of a hotel.

It consists of the ground floor, the first floor, the second floor and the third floor.

The whole installation is carried out in accordance to the following requirements:

- (1) The 16th edition of the IEE wiring regulations and additional local regulation.
- (2) EAC Conditions of supply
- (3) C.I.B.S. code for interior lighting
- (4) Interior lighting design.
- (5) CYTA regulations

ASSUMPTIONS

- (1) Supply Voltage: 415Vrms, 50Hz, TT earthing system.
- (2) Wiring method: PVC conduit (method 3)
- (3) Earth conduit carries one cct only, so grouping factor $C_g=1$
- (4) Ambient temperature is assumed to be 30°C so ambient temperature factor $C_a=1$.
- (5) Thermal insulation is not used, so insulation factor $C_i=1$.
- (6) External earth fault loop impedance= 0.5Ω